



## MIDI EXCAVATOR

## **SV60**



Weight

Operating weight 5.635 kg Transport weight 5.560 kg

Yanmar 4TNV84T-ZMBVA

32,6 kW at 2200 rpm

12 V - 100 Ah

2,2 / 4,7 km/h

24,8 kN / 27,3 kN

10 rpm

41,9 kN

245 bar

10,8 l/min

0,31 kgf/cm<sup>2</sup>

100 I

7,1 I

7,41

74 I

38 I

2 x 45,8 l/min 37 I/min

150 - 163 N.m. at 1700 rpm (± 100 rpm)

Lwag = 95 dB(A); Lpag = 79 dB(A)

Diesel

1,995 I

**Engine** 

Type Fuel Displacement . Maximum torque Net power Battery

**Performance** 

Travelling speed

Rotation speed Digging force (long arm / short arm) Digging force (bucket) Gradeability

Noise level

(2000/14/CE & 2005/88/CE)

**Hydraulic system** 

Maximum pressure 1 double piston pump with variable flow

1 gear pump

1 gear pump for pilot line

**Undercarriage** 

Number of top roller Number of bottom rollers Track tensioning system Ground pressure

**Capacities** 

Fuel tank Cooling fluid Engine oil Hydraulic circuit Hydraulic tank

**Available equipment** 

Short / long arm Rubber / steel crawlers Cabin FOPS II

Full cylinders protection in standard

3rd & 4th proportional circuits with flow control

3 safety valves

PVC or fabric seat with pneumatic suspension

Air conditioning / heater

Additional counterweight (+200 kg)

Line for hydraulic quick hitch

Eco-Mode

Auto-Deceleration

Refueling pump

Improved filtration

Circuit derivation

2 LED working lights on the front of the cabin

1 LED working light at the back of the cabin + beacon

Beacon lights

Rearview camera in standard

Radio

## **Dimensions**





